CLAIMS

What is claimed is:

5

6

7

8

9

1

2

[] 3

5

1

2

3

4

5

1

- 1 1. A method of constructing a lookup table of modes for 2 encoding data for transmission in a wireless communication 3 channel from a transmit unit to a receive unit, said method 4 comprising:
 - a) selecting at least one quality parameter of said data as received by said receive unit;
 - b) determining a first-order statistical parameter of said at least one quality parameter;
 - c) determining a second-order statistical parameter of said at least one quality parameter; and
 - d) arranging said modes in said lookup table based on said first-order statistical parameter and based on said second-order statistical parameter.
 - 2. The method of claim 1, wherein said first-order statistical parameter and said second-order statistical parameter are determined from a simulation of said wireless communication channel.
 - 3. The method of claim 1, wherein said first-order statistical parameter and said second-order statistical parameter are determined from a field measurement of said wireless communication channel.
 - 4. The method of claim 1 further comprising:
 - a) selecting a communication parameter;

	3		
	4		
	5		
	6		
	7		
	1		
	2		
	3		
	4		
	5		
	6		
	1		
A. H. H. H. H.	2		
٦,	3		
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	4		
ζN	1		
	3		
# ! !			
	5		
	_		
or Hill	7		
	8		
	a		

- b) setting a target value of said communication parameter; and
- c) arranging said modes in said lookup table based on said target value.
- 5. The method of claim 4, wherein said communication parameter is selected from the group consisting of bit error rate, packet error rate, data capacity, signal quality, spectral efficiency and throughput.
- 6. The method of claim 4, wherein said communication parameter is a statistical communication parameter.
- 7. The method of claim 4, further comprising:
 - a) measuring a measured value of said communication parameter in said wireless communication channel;
 - b) assigning an adjustment to at least one of said first-order statistical parameter and said second-order statistical parameter based on a difference between said measured value and said target value.
- 8. The method of claim 1, wherein said quality parameter is a short-term quality parameter.

1

- 9. The method of claim 8, wherein said second-order statistical parameter comprises a variance of said short-term quality parameter.
 - 10. The method of claim 9, wherein said variance is selected from the group consisting of temporal variance and frequency variance.
- 11. The method of claim 8, wherein said short-term quality parameter is selected from the group consisting of signal-to-interference and noise ratio, signal-to-noise ratio and power level.
- 12. The method of claim 1, wherein said first-order statistical parameter comprises a mean of said at least one quality parameter.
- 13. The method of claim 1, wherein said second-order statistical parameter comprises a variance of said at least one quality parameter.
 - 14. The method of claim 13, wherein said data is transmitted at more than one frequency and said variance is a frequency variance.
 - 15. The method of claim 13, wherein said data is transmitted in a multi-carrier scheme and said variance is a frequency variance.

1			16. The method of claim 13, wherein said variance is		
2			a temporal variance.		
3					
1		17.	The method of claim 1, wherein said transmitting step		
2			is performed in accordance with a transmission		
3			technique selected from the group consisting of OFDMA,		
4			FDMA, CDMA, TDMA.		
5					
1	18.	A storage medium tangibly embodying a lookup table of modes			
2		for	encoding data for transmission in a wireless		
3		comm	unication channel from a transmit unit to a receive		
4		unit	, said storage medium comprising instructions for:		
111 111 111		a)	selecting at least one quality parameter of said data		
146			as received by said receive unit;		
100 mile 113		b)	determining a first-order statistical parameter of		
### ### 8			said at least one quality parameter;		
*		c)	determining a second-order statistical parameter of		
1 0			said at least one quality parameter; and		
# 41		d)	arranging said modes in said lookup table based on		
12			said first-order statistical parameter and based on		
1 3			said second-order statistical parameter.		
14					
1		19.	The storage medium of claim 18, further comprising		
2			instructions for:		
3			a) selecting a communication parameter;		
. 4			b) setting a target value of said communication		
5			parameter; and		
6			c) arranging said modes in said lookup table based		

on said target value.

6

Hone from which find give given my of weath from firth the top of weath from firth the top of weath from firth given from the first weath the top of weath from the first weath the top of weath from the first weath the first weath the first weath from the first

- 20. The storage medium of claim 19, further comprising instructions for:
 - a) measuring a measured value of said communication parameter in said wireless communication channel;
 - b) assigning an adjustment to at least one of said first-order statistical parameter and said second-order statistical parameter based on a difference between said measured value and said target value.